

2W54E 20 BAR MULTIPURPOSE / HOT WATER DELIVERY

Multipurpose hose for wide range of water transport applications. Including hot water



Temperature range:	-40°C. +120°C.
Electrical continuity:	N/A.
Lining:	Black synthetic rubber (EPDM).
Reinforcement:	High tenacity polyester tyre cord.
Cover:	Black smooth synthetic rubber (EPDM).
Brand:	As per customer requirements.
Ends:	Vulcanized Beaded Type (Swivel) Flanges
Options:	See page 214 for fitting options.

Hose article	Inside diameter	Outside diameter	Wall thickness	Working pressure	Burst pressure	Test pressure	Vacuum pressure	Min. bend. radius	Hose weight	Assy weight	Max. avail. length
Nº	mm	mm	mm	bar	bar	bar	bar	mm	kg/m	kg/10m	m
2W54E-203	203	229.4	13.2	20	60	30	-	-	12	145	61
2W54E-254	254	278.0	12.0	20	60	30	-	-	13	164	12
2W54E-305	305	333.2	14.1	20	60	30	-	-	19	223	12
2W54E-356	356	402.8	23.4	20	60	30	-	-	39	444	12
2W54E-406	406	455.2	24.6	20	60	30	-	-	46	540	12
2W54E-456	456	514.2	29.1	20	60	30	-	-	62	721	12
2W54E-508	508	569.8	30.9	20	60	30	-	-	74	861	12
2W54E-610	610	677.2	33.6	20	60	30	-	-	95	1108	12

Norms: ISO 1307