


2W54-S 20BAR HEAVY DUTY WATER DELIVERY HOSE.

Heavy duty water delivery hose.



Temperature range:	-30°C +80°C.
Electrical continuity:	N/A.
Lining:	Black synthetic rubber (SBR).
Reinforcement:	High tensile polyester tyre cord.
Cover:	Black smooth synthetic rubber (SBR). Abrasion and weather resistant.
Working pressure:	20 Bar. 3:1 Safety factor.
Vacuum pressure:	N/A.
Brand:	As per customer request.
Ends:	Plain ends.

Options:

Hose article	Inside diameter	Outside diameter	Wall thickness	Working pressure	Burst pressure	Min. bending radius	Hose weight	Max. available length
Nº	mm	mm	mm	bar	bar	mm	kg/m	m
2W54-S-032	32	41.8	4.9	20	60	-	0.84	61
2W54-S-038	38	47.8	4.9	20	60	-	0.98	61
2W54-S-051	51	61.2	5.1	20	60	-	1.30	61
2W54-S-063	63	73.2	5.1	20	60	-	1.57	61
2W54-S-076	76	88.4	6.2	20	60	-	2.20	61
2W54-S-102	102	117.6	7.8	20	60	-	3.66	61
2W54-S-127	127	142.6	7.8	20	60	-	4.49	61
2W54-S-152	152	170.6	9.3	20	60	-	6.19	61
2W54-S-203	203	224.0	10.5	20	60	-	9.45	61
2W54-S-254	254	278.0	12.0	20	60	-	13.11	12
2W54-S-305	305	334.4	14.7	20	60	-	19.26	12

Norms: ISO1307