2W58-LF 16BAR LAYFLAT WATER DELIVERY HOSE.

Lightweight water delivery hose.



Temperature range:	-30°C +90°C.
Electrical continuity:	N/A.
Lining:	Black chloroprene rubber (CR).
Reinforcement:	High tensile polyester tyre cord.
Cover:	Black smooth chloroprene rubber (CR), oil, abrasion and weather resistant.
Working pressure:	16 Bar. 3:1 Safety factor.
Vacuum pressure:	N/A.
Brand:	As per customer request.
Ends:	Plain ends.
Options:	EPDM (for acidic water) or NBR (for water with traces of fuel/oil) liners available on request.

Hose article	Inside diameter	Outside diameter	Wall thickness	Working pressure	Burst pressure	Min. bending radius	Hose weight	Max. available length
№	mm	mm	mm	bar	bar	mm	kg/m	m
2W58-LF-051	51	58.2	3.6	16	48	-	0.86	61
2W58-LF-063	63	70.4	3.7	16	48	-	1.05	61
2W58-LF-076	76	83.8	3.9	16	48	-	1.29	61
2W58-LF-102	102	109.8	3.9	16	48	-	1.71	61
2W58-LF-127	127	137.0	5.0	16	48	-	2.82	61
2W58-LF-152	152	165.2	6.6	16	48	-	4.45	61

Norms: ISO1307